









 <p>The diagram illustrates a standard intersection layout. At the center is a green square representing the intersection, surrounded by a red and white striped border. Four blue circular signs with white arrows (C4a) are positioned at the corners, indicating the direction of traffic flow. Yellow circular signs with a '1' (A15) are placed at the corners of the intersection. The signs are labeled 'A15' and '1'. The central area is labeled 'ZZ'. The signs are labeled 'C4a' and 'ZZ'.</p>	<h2>Schéma B/14.2</h2> <h3>Standardní pracovní místo v prostoru křižovatky.</h3> <hr/> <p>vedení provozu (užití značek č. C 4 a až č. C4 c) závisí na konkrétním umístění pracovního místa v prostoru křižovatky, případně se pro určitý směr zřizuje objížďka</p> <p>příčné uzávěry zábranou minimálně 3 výstražná světla typu 1</p> <p>výstražné světlo typu 1 nebo značka umístěna na fluorescenčním žlutozeleném podkladu, u ostatních vjezdů shodně</p> <p>1) minimální šířka se zjišťuje pomocí vlečných křivek</p> <p>Pozn.: Pro usměrnění provozu v prostoru křižovatky lze užít směrovacích desek (č. Z4a až č. Z4c) dle konkrétní situace</p> <p>vzdálenosti v metrech</p>
---	--





















